

## 1998-2006 HARRIS SET UP SHEET:



### AIR PRESSURES:

LF: 12 / RF: 15 / LR: 10 / RR: 15

STAGGER: 1" FRONT | 2" REAR

### FRONTEND SETTINGS:

CASTER: LF +1.5 | RF +3.5 CAMBER: LF +3 | RF -4 TOE OUT: 1/8"

### 4-LINK ROD LENGTHS & POSITIONS:

LT: 17" C-C 3<sup>rd</sup> UP | RT: 17" C-C 3<sup>rd</sup> UP  
LB: 15" C-C 4<sup>th</sup> UP | RB: 15" C-C 3<sup>rd</sup> UP

J-BAR: START @ 23.5" 6" UP ON FRAME | CENTER OF PINION

### 2-LINK ROD LENGTHS & POSITIONS

LEFT: 16" or 20 1/2" C-C 4<sup>th</sup> UP | RIGHT: 20 1/2" C-C 3<sup>rd</sup> UP

PANHARD BAR: 14 DEGREES | 3" BELOW CENTER OF AXLE

PULL BAR: 7 - 8.5 DEGREES PINION ANGLE

2<sup>ND</sup> HOLE UP ON HOUSING | 2<sup>ND</sup> HOLE UP ON FRAME

### SPRINGS:

LF: 600# | RF: 650# | LR: 13"/16" 200# | RR: 11"/13" 200#

### RIDE HEIGHTS:

LF: 14 1/2" | RF: 15" | LR: SET WEDGE | RR: 2 3/4" (BOTTOM OF AXLE TO TOP OF RR UNDERRAIL)

PERCENTAGES: \*WITH THE DRIVERS WEIGHT IN THE SEAT

LEFT SIDE %: 54.0 / REAR %: 56.0 / WEDGE: 30 - 100 #